



便利調整手輪 & 位置顯示器

Convenient position adjusting device & Position indicator

7 吋彩色觸控人機  
7" Color touch screen (HMI)

熱燙印字機 & 可調支撐座 (選配)  
Hot stamping printer & Adjustable support rack (optional item)

腳架式貼標機搭配上貼貼標機  
Support stand type labeling machine  
Combine with Flat-surface Top labeling machine

## LA-101 腳架式貼標機 (上貼 / 側貼)

### Support-stand Type Labeling Machine (Top-labeling / Side-labeling)

#### 適用範圍

- 產品上方或側面之平面貼標，適合：方瓶 / 紙盒...等產品。
- 適用多種標籤尺寸，同時適用透明標籤。
- 適合搭配現有之輸送帶，每日產能較大與產品多樣化的生產需求。

#### 特色介紹

- 日本三菱 PLC，搭配 7 吋彩色人機觸控螢幕，操作簡易。
- 出標系統採用步進馬達，貼標精準度高，易於校正控制。
- 貼標系統：德國大廠 SICK 感測器 (電眼)，品質穩定、感應準確。
- 便利手輪裝置搭配位置顯示器，輕鬆調整與記錄貼標位置。
- 內建 50 組記憶模組，適合生產多種產品，不需重覆輸入設定。
- 使用者友善介面：多種免工具調整設計，換線快速。

#### 機台規格

機台尺寸	1000(長) x 910(寬) x 1400(高) mm
動力需求	電壓 110V，頻率 50/60Hz，單相，功率 150VA
適用標籤高度	(A 型)10~100 (B 型)10~150 (C 型)10~200 mm
適用標籤長度	15 ~ 200 mm
機台產能	約 10 ~ 60 個 / 每分鐘
貼標精度	± 1.0 mm
印字設備 (選配)	熱燙印字機 / 熱轉印機 / 噴印機 (印日期、批號、條碼... 另含可調整支撐座)

#### Field of Application

- Labeling on the top or side flat surface of various square bottles, boxes...etc.
- A wide range of label size, transparent labels are also applicable.
- Suitable to combine existing conveyor.
- Suitable for larger quantity but with wide range of products producing demands.

#### Features

- Japan Mitsubishi PLC and 7" color touch screen (HMI) provide convenient operation.
- Stepper motor in labeling system offers the high labeling precision.
- Labeling system: Stepper motor and SICK (German brand) sensor for high labeling precision and easy adjustments.
- Adjust and record the labeling position conveniently by a hand-wheel device combined with a position indicator.
- 50 sets of memory storage: Perfect for various products without repeated setting.
- User-friendly interface: Quick changeover design helps most adjustments can be finished without using tools.

#### Specifications

Machine Dimension	1000(L) x 910(W) x 1400(H) mm
Power Requirement	110V, 50/60Hz, 1 Phase, 150VA
Applicable Label Height	(A) 10~100 (B) 10~150 (C) 10~200 mm
Applicable Label Length	15 ~ 200 mm
Production Capacity	About 10 ~ 60 PCS/per minute
Labeling Precision	± 1.0 mm
Printers (optional item)	Hot Stamping / Heat Transfer / Inkjet (Date, Batch no., Barcode... Support rack included)