



貼標便利調整手輪
& 位置顯示器
Convenient adjusting
device for labeling
& Position indicator

4.3 吋彩色觸控人機
4.3" Color touch screen (HMI)

工作台車 (含腳輪)
Working table (with castors)

熱燙印字機 & 可調支撐座
(選配項目)
Hot stamping printer & Adjustable rack
(optional item)

德國 SICK 電眼
SICK sensor (German brand)

LA-105 半自動平面上貼標機

Semi-automatic Flat-surface Top Labeling Machine

適用範圍

- 適合小尺寸扁平狀產品貼標，如：紙盒 / 塑料袋 / 面膜袋 / 卡片與說明書等紙本類之各式產品。
- 適用多種標籤尺寸，亦適用透明標籤。
- 最適合「少量多樣」的貼標需求。

特色介紹

- 日本三菱 PLC，搭配 4.3 吋彩色人機觸控螢幕，操作簡易。
- 出標系統採用步進馬達，貼標精準度高，易於校正控制。
- 便利手輪裝置搭配德國品牌之位置顯示器，可精確調整貼標位置且輕鬆不費力。
- 內建 50 組記憶模組，適合生產多種產品，不需重覆輸入設定。
- 使用者友善介面：快拆模組與多種免工具調整設計，換線快速。
- 德國 SICK 電眼自動感應啟動貼標。
- 可選配「熱轉印機 / 噴印機」，多家國際知名廠牌供選擇。

機台規格

| | |
|-----------|---|
| 機台尺寸 | 1200(長) x 655(寬) x 1586(高) mm |
| 動力需求 | 電壓 110V，頻率 50/60Hz，單相，視在功率 60VA |
| 適用標籤高度 | (A 型)10~100 (B 型)10~150 mm |
| 適用標籤長度 | 10 ~ 200 mm |
| 機台產能 | 約 10 ~ 15 米 / 每分鐘 |
| 貼標精度 | ± 1.0 mm |
| 印字設備 (選配) | 熱燙印字機 / 熱轉印機 / 噴印機 (印日期、批號、條碼... 另含可調整支撐座) |

Field of Application

- Labeling on flat surface of various small-sized products, such as unfolded boxes, plastic pouches, cards, etc.
- A wide range of label size, transparent labels are also applicable.
- Most suitable for various products but small-volume daily production.

Features

- Japan Mitsubishi PLC and 4.3" color touch screen (HMI) provide convenient operation.
- Stepper motor in labeling system offers the high labeling precision.
- Adjust and record the labeling position conveniently and precisely by a hand-wheel device combined with position indicator.
- 50 sets of memory storage: Perfect for various products without repeated setting.
- User-friendly interface: Quick changeover design helps most adjustments can be finished without using tools.
- SICK photoelectric sensor (German brand) for labeling start-up.
- Compatible with Thermal Transfer Printer or Inkjet Printer. Many famous brands of printer are available to be integrated.

Specifications

| | |
|--------------------------|--|
| Machine Dimension | 1200(L) x 655(W) x 1586(H) mm |
| Power Requirement | 110V, 50/60Hz, 1 Phase, 60VA |
| Applicable Label Height | (A) 10~100 (B) 10~150 mm |
| Applicable Label Length | 10 ~ 200 mm |
| Production Capacity | About 10 ~ 15 meters /per minute |
| Labeling Precision | ± 1.0 mm |
| Printers (optional item) | Hot Stamping / Heat Transfer / Inkjet (for Date, Batch no., Barcode... Support rack included) |