



熱燙印字機 & 可調支撐座 (選配)  
 Hot stamping printer & Adjustable support rack (optional item)



分瓶輪  
 Bottle separation wheel



上下調整手輪 & 位置顯示器  
 Up / Down adjusting device & Position indicator



定點貼標裝置  
 Positioning labeling device



前後調整手輪 & 位置顯示器  
 Front/Back adjusting device & Position indicator



## LA-250 自動圓瓶貼標機 (定點式)

### Automatic Round Bottle Labeling Machine (Positioning type)

#### 適用範圍

- 圓瓶之單張全繞貼、半繞貼或連續出標 2 張 (正標 + 背標)。
- 適用多種標籤尺寸, 亦適用透明標籤。
- 通用各材質且多種尺寸之圓瓶: 塑膠瓶、玻璃瓶、金屬瓶。
- 適合產品多樣化的貼標需求, 可連線生產或單機使用。

#### 特色介紹

- 定點式環繞貼標, 確保標籤兩端完美對齊、不皺摺不歪斜。
- 日本三菱 PLC, 搭配 7 吋彩色人機觸控螢幕, 操作簡易。
- 出標系統採用步進馬達, 貼標精準度高, 易於校正控制。
- 便利手輪裝置搭配位置顯示器, 輕鬆調整與記錄貼標位置。
- 50 組記憶模組, 適合生產多種產品, 不需重複輸入設定。
- 可選配「熱轉印機/噴印機」, 多家國際知名廠牌供選擇。

#### 機台規格

機台尺寸	1800(長) x 1060(寬) x 1530(高) mm
動力需求	電壓 110V, 頻率 50/60Hz, 單相, 視在功率 270VA
需求空壓	4kg/cm <sup>2</sup> 以上 (請自備空壓來源)
適用標籤高度	(A 型)10~100 (B 型)10~150 (C 型)10~200 mm
適用標籤長度	10 ~ 300 mm
機台產能	約 10 ~ 30 瓶 / 每分鐘
貼標精度	± 1.0 mm
選配項目	(1) 熱燙印字機 / 熱轉印機 / 噴印機 (印日期、批號、條碼... 另含可調整支撐座) (2) 光學檢測系統 / 不良標預先剔除裝置 (3) 自動進瓶 / 收瓶轉盤

#### Field of Application

- One label of full and partial wrap-around or continuous two labels as front & back label for round bottles.
- A wide range of label sizes, also applicable for transparent labels.
- Various round bottle dimensions & material: Plastic, glass & metal bottles.
- Many kinds of round bottles are applicable for a packaging production line or separate operation.

#### Features

- Positioning wrap-around labeling ensures 2 ends of label to be aligned perfectly.
- Japan Mitsubishi PLC and 7" color touch screen (HMI) provide convenient operation.
- Stepper motor in labeling system offers the high labeling precision.
- Adjust and record the labeling position conveniently by a hand-wheel device combined with a position indicator.
- 50 sets of memory storage: Perfect for various products without repeated setting.
- Compatible with Thermal Transfer Printer or Inkjet Printer. Many famous brands of printer are available to be integrated.

#### Specifications

Machine Dimension	1800(L) x 1060(W) x 1530(H) mm
Power Requirement	110V, 50/60Hz, 1 Phase, 270VA
Pneumatic Requirement	4kg/cm <sup>2</sup> at least (prepared by buyer)
Applicable Label Height	(A) 10~100 (B) 10~150 (C) 10~200 mm
Applicable Label Length	10 ~ 300 mm
Production Capacity	About 10 ~ 30 PCS / per minute
Labeling Precision	± 1.0 mm
Optional item	(1) Hot Stamping / Heat Transfer / Inkjet Printer (for Date, Batch no., Barcode... Support rack included) (2) Optical inspection system / Pre-rejection of defective label (3) Automatic bottle feeding / collection turntable